

The present invention relates to a tool coupling comprising a holder (1), an adapter (3; 3') for at least one cutting insert for chip removing machining and a separate element (5; 5') in order to detachably connect the holder (1) and the adapter (3; 3') with each other, said holder (1) being provided with a first serration (12), having mutually parallel grooves, and the adapter (3; 3') being provided with a second serration (16), having mutually parallel grooves. The invention also relates to the holder (1) and the adapter (3; 3') per se. It is significant for the tool coupling according to the present invention that the first serration (12) is located in a plane having an extension essentially perpendicular to a longitudinal centre axis (13) of the tool coupling, and that the second serration (16) is located in a plane having an extension essentially perpendicular to said longitudinal centre axis (13).

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZV	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## TOOL COUPLING

Technical Field of the Invention

5 The present invention relates to a tool coupling comprising a holder, an adapter for at least one cutting insert for chip removing machining and a separate element in order to detachably connect the holder and the adapter with each other, said holder being provided with a first serration having mutually parallel grooves, and the adapter being provided with a second serration having mutually parallel grooves. The invention also  
10 relates to the holder and the adapter per se.

Prior Art

From WO 93/10929 a turning tool is previously known, said turning tool having a  
15 cylindrical shaft and a head having a contact surface that rests against a support surface of the shaft. The contact surface and the support surface are arranged at an acute angle relative to the longitudinal centre axis of the tool and each of said surfaces is provided with serrations having mutually parallel grooves, said serrations engaging each other when the contact surface and the support surface are resting against each other. In order  
20 to connect the shaft and the head with each other holes are provided in said elements, said holes extending essentially perpendicular to said surfaces and are located directly opposite to each other when the contact surface and the support surface are resting against each other in correct position. A threaded screw is received in said holes in order to urge the surfaces against each other and provide a reliable connection between  
25 the shaft and the head.

The holes in the shaft and the head are designed in such a way that they have a larger cross dimension in a direction perpendicular to the serrations than in the longitudinal direction of the serrations. By this arrangement it is achieved that the serrations guide  
30 the mutual orientation of the shaft and the head in a direction perpendicular to the longitudinal direction of the grooves while the fit of the hole relative to the screw guides the mutual orientation of the shaft and the head in a direction parallel to the longitudinal direction of the grooves.

35 Since the contact surface and the support surface form an angle with the longitudinal centre axis of the tool also the threaded screw that connects the shaft with the head forms an angle with said longitudinal centre axis. This arrangement causes problems as

regards the provision of cooling passages that have to be located eccentrically in the shaft. Especially in connection with rotating tools it is not beneficial to locate the cooling passages eccentrically. Said eccentric location of the cooling passages also brings about that the shaft may not be used both for right-hand type tools and left-hand type tools.

### Objects and Features of the Invention

The object of the present invention is to set aside the disadvantages of known tool couplings and create a tool coupling that is usable for different types of chip removing machining, e.g. milling, turning and drilling.

A primary object of the invention is that the tool coupling should be usable in connection with tools that rotate at an extremely high speed, i.e. the tool coupling should not generate vibrations or the like due to unbalance of said tool coupling.

Still an object of the invention is that the tool coupling should make it possible for the holder and the adapter to be connected with each other by means of simple connecting means, preferably of standard type.

A further object of the invention is that the tool coupling generally should be usable both for tools of right-hand type and left-hand type.

The objects of the invention are realised by means of a tool coupling that has been given the features of the appending claims. Especially, preferred embodiments of the invention are defined in the dependent claims.

### Brief Description of the Enclosed Drawings

Below preferred embodiments of the tool coupling according to the present invention will be described, reference being made to the accompanying drawings, where:

- Figure 1 shows a perspective view of a first embodiment of a tool coupling according to the present invention, said view being taken obliquely from behind of the holder;
- Figure 2 shows a perspective view of the tool coupling according to figure 1, said view being taken obliquely from the front of the adapter;

- Figure 3 shows a side view of the tool coupling according to figure 1;  
 Figure 4 shows a top view of the tool coupling according to figure 1;  
 Figure 5 shows a section along A-A in figure 4;  
 Figure 6 shows a section along B-B in figure 4;  
 5 Figure 7 shows a perspective view of the second embodiment of a tool coupling according to the present invention, said view being taken obliquely from behind of the holder;  
 Figure 8 shows a perspective view of the tool coupling according to figure 7, said view being taken obliquely from the front of the adapter;  
 10 Figure 9 shows a side view of the tool coupling according to figure 7;  
 Figure 10 shows a top view of the tool coupling according to figure 7;  
 Figure 11 shows a section along C-C in figure 10;  
 Figure 12 shows a section along D-D in figure 10; and  
 Figure 13 shows in a larger scale a preferred elliptic cross section of the centre  
 15 holes in the holder and the adapter.

#### Detailed Description of Preferred Embodiments

The first embodiment of a tool coupling according to the present invention, shown in  
 20 figures 1-6, comprises a holder 1, an adapter 3 and a connecting element in the shape of a stud screw 5 having a first external thread 7 at one end and a second external thread 9 at its other end. In the shown embodiment the threads 7, 9 run in the same direction but have different pitch, the second external thread 9 having a larger pitch than the first external thread 7. The stud screw 5 is also provided with key recesses 10 and 11  
 25 respectively at its both ends. From figures 5 and 6 it is evident that the stud screw 5 is provided with an axially extending, through going, first cooling passage 6 that is located in the centre of the stud screw 5.

As is most evident from figure 2 the holder 1, at one of its axial end surfaces, is  
 30 provided with a first serration 12 having grooves extending parallel to each other. Said axial end surface of the holder 1 is generally planar and has an extension perpendicular to a longitudinal centre axis 13, see figure 5, of the tool coupling, said axis 13 also constituting a longitudinal centre axis of the holder 1 and the adapter 3. As is most evident from figure 5 the holder 1 is provided with an internal, through going, first  
 35 centre hole 14 having sections of different diameter, the section of the first centre hole 14, located closest to the end surface having the first serration 12, is provided with a first internal thread 15. In this connection it should be pointed out that the design of

said first centre hole 14, in the area of the end facing away from a the first serration 12, may vary to a great extent depending on which type of holder 1 that is used in the actual case. In the embodiment shown in figures 1-6 a holder 1 is used that is part of a holder system manufactured under the trade name of COROMANT CAPTO®.

5

As is most evident from figure 1 the adapter 3, at one of its axial end surfaces, is provided with a second serration 16 having grooves extending parallel to each other. Said axial end surface of the adapter 3 being generally planar and having an extension perpendicular to a longitudinal centre axis 13, see figure 5, of the tool coupling. As is most evident from figure 5 the adapter 3 is provided with an internal, not through going, second centre hole 17 that has an internal second thread 18. From said second centre hole 17 a number of second cool passages 19 extend radially outwards in order to emerge in the seats of the cutting inserts of the adapter 3.

15 Reference is being made to figure 13 as regards the cross sectional shape of the holes 14 and 17, in the area adjacent the axial end surfaces having the serrations 12, 16. Generally, said holes 14, 17 have an oval or out of round cross section, said cross section having a larger cross dimension in the direction perpendicular to the grooves of the serrations 12, 16 than the cross dimension parallel to the grooves of the serrations 20 12, 16. Preferably, the cross section of the holes 14, 17 is elliptic in the actual area, a preferred elliptic cross section is shown in figure 13. In this connection it should be reminded that the equation of the ellipse is the following:  $x^2/a^2 + y^2/b^2 = 1$ . A preferred relation for  $a/b = 0.95-0.99$ . A preferred value for  $a = 2-10$  mm.

25 The ovality of the holes 14, 17 may be achieved by means of an end mill subsequent to the provision of the basic shape of the holes 14, 17, e.g. by means of a reamer.

In the embodiment according to figures 1-6 the adapter 3 being designed as a milling head that is provided with a number of cutting insert seats. As has been pointed out 30 above, said second cooling passages 19 emerge in said cutting insert seats.

When the tool coupling according to the present invention is transferred to active position the stud screw 5 is threaded into the holder 1, i.e. the first external thread 7 engages a first internal thread 15. Then the adapter 3 is threaded on the projecting 35 portion of the stud screw 5 that hereby is fixed against rotation, i.e. the second external thread 9 engages the second internal thread 18. Alternatively, the stud screw 5 may be threaded into the adapter 3 and the holder 1 threaded on the projecting portion of the

stud screw 5. However, in this case it is more difficult to lock the stud screw 5 against rotation. The axial end surfaces, having serrations 12, 16, will be located adjacent each other but at some distance from each other. In this connection it should be pointed out that the groove configuration of the respective serrations 12, 16 has a mutually adapted design, i.e. the angles of the flanks of the threads are the same.

Then the mutual connection of the holder 1 and the adapter 3 proceeds by having the stud screw 5 rotated in the direction that causes the stud screw 5 to be displaced further into the second centre hole 17. In this connection it is supervised that the grooves of the respective serrations 12, 16 are oriented parallel to each other. Said displacement of the stud screw 5 in the second centre hole 17 brings about, due to the different pitch of the external threads 7 and 9 respectively and the internal threads 15 and 18 respectively, that the holder 1 and the adapter 3 are pushed together until the serrations 12, 16 are in complete engagement with each other. At a certain rotation of the stud screw 5, said stud screw 5 will be displaced a longer distance relative to the adapter 3 than relative to the holder 1. When the connection between the holder 1 and the adapter 3 is to be terminated the stud screw 5 is rotated in the opposite direction compared to when the connection is established.

In the connecting phase when the serrations 12, 16 come into engagement with each other the oval cross section of the holes 14 and 17, adjacent said serrations 12, 16, is of importance, see figure 6. The smallest cross dimension of the holes 14, 17, in a direction parallel to the grooves of the serrations 12, 16, has a precise slide fit relative to the diameter of the stud screw 5. This means that the holes 14, 17 and the stud screw 5 guide the mutual orientation of the holder 1 and the adapter 3 in the direction parallel to the grooves of the serrations 12, 16. In the direction perpendicular to the grooves of the serrations 12, 16 the cooperation between the respective serrations 12, 16 guides the mutual orientation between the holder 1 and the adapter 3. This being enabled due to the fact that the holes are oval in said direction perpendicular to the grooves of the serrations 12, 16.

In figure 6 the sector P is drawn, within which slide fit exists between the stud screw 5 and the holes 15 and 17, and in figure 6 also the sector S is drawn, within which there is a gap T between the stud screw 5 and the holes 15 and 17. A suitable interval for the sector  $P = 30^\circ - 50^\circ$  and for the sector  $S = 120^\circ - 150^\circ$ . Generally,  $P + S = 180^\circ$ . Suitable value of the gap  $T = 0.05 - 0.5$  mm.

The holder 1 and the adapter 3 are thus brought to assume the mutual position that is shown in figures 3-5. In this connection it should be pointed out that in said mutual position of the holder 1 and the adapter 3 the axial distance between the two external threads 7 and 9 essentially correspond to the axial distance between the two internal threads 15 and 18.

As is evident from figures 5 and 6 the stud screw 5 is provided with an axial, through going, first cooling passage 6. Cooling medium that is supplied at the right end of the stud screw 5 in figure 5 thus exits at the left end of the, not through going, second centre hole 17 in figure 5. From there the cooling medium is further transmitted via the second cooling passages 19 that emerge in the cutting insert seats of the adapter 3 designed as a milling head.

The alternative embodiment of the tool coupling according to the present invention, shown in figures 7-12, differs from the embodiment described above primarily in that the connecting element 5' is designed as a screw having a first external thread 7' at one end and a head 8' at its other end. At said other end the screw 5' is provided with a key recess 11'. The first external thread 7' is intended to be received in a holder 1 that could be identical with the holder 1 described above. This is of course a benefit of the tool coupling according to the present invention.

As is most evident from figure 11 the screw 5' is provided with an axially extending, not through going, first cooling passage 6' that extends from and penetrates the end of the screw 5' that is equipped with the first external thread 7'. The first cooling passage 6' terminates at a distance from the end of the screw 5' that is equipped with a key recess 11'. A number of branch cooling passages 21' start from said first cooling passage 6', in the area where said cooling passage 6' terminates at distance from the key recess 11', said branch cooling passages 21' penetrating the circumferential surface of the screw 5', see figures 7 and 8. As is evident from figures 7, 8 and 11 the screw 5' is provided with a waist, i.e. a reduction of diameter, in the area where the branch cooling passages 21' emerge. Thereby, a space is created for the cooling medium between the screw 5' and the second centre hole 17'. The first cooling passage 6' is located in the centre of the screw 5'.

The adapter 3' of the embodiment according to figures 7-12 is also in the shape of a milling head, said adapter 3' being intended to cooperate with the head 8' of the screw 5'. For this reason the adapter 3' has certain structural differences compared to the



adapter 3 according to figures 1-6. However, the serration 16 provided at one axial end surface is in principle identical with the first serration 16 of the embodiment according to figures 1-7. Also the extension of said axial end surface corresponds to the embodiment according to figures 1-7.

As this most evident from figure 11 the second centre hole 17' in the adapter 3' is through going without having any internal thread. The second centre hole 17' has a shoulder 20' in the area of the end of the adapter 3' where the cutting insert seats are located, said shoulder 20' being intended to cooperate with the head 8' of the screw 5'.

In correspondence to the embodiment according to figures 7-12 second cooling passages 19' are provided in the adapter 3', said second cooling passages 19' extending radially from the second, through going, centre hole 17' and emerge in the cutting insert seats of the adapter 3', see for instance figure 9. Cooling medium that is supplied at the right end of the screw 5' in figure 11 thus flows through the first cooling passage 6', through the branch cooling passages 21', out into the space between the portion of the screw 5' having reduced diameter and the second centre hole 17' and through the second cooling passages 19'.

When the tool coupling according to the embodiment shown in figures 7-12 is transferred to active position the holder 1 and the adapter 3' are located relative to each other as is shown in figures 9-11, i.e. the respective serrations 12, 16 are in engagement with each other. Then the screw 5' is inserted from the left end in figure 11, i.e. the screw 5' extends through the second centre hole 17' and its external first thread 7' is brought into engagement with the internal thread 15 of the holder 1'. Through suitable tightening of the screw 5' a proper mutual connection is achieved between the holder 1 and the adapter 3'. When the connection is to be terminated the screw 5' is rotated in opposite direction. In this connection it should be mentioned that the mutual relation between the cross section of the screw 5' and the cross sections of the holes 15 and 17', see for instance figure 12, in principle corresponds to the relation that exists between the cross section of the stud screw 5 and the cross sections of the holes 15 and 17, and therefore reference is made to what has been said above regarding the effects of said cross section relation. As regards the extension of the sectors for fit and gap reference is also made to figure 6 and adherent passages in the description above. The corresponding is also valid for the preferred cross section design that is shown in figure 13, i.e. said design is also valid for the hole 17'.

Preferably, the tool coupling described above is symmetrical in relation to its longitudinal centre axis 13, which means that the holder may be used both for tools of right-hand type and left-hand type. In certain special applications, for instance in connection with certain special types of turning, it may be preferable if the adapter 3; 3' may be rotated 180° relative to the holder 1. This may be effected by the tool coupling according to the present invention.

#### Feasible Modifications of the Invention

10 In the embodiment according to figures 1-7 the internal, second centre hole 17 is not through going. However, within the scope of the invention it is feasible that said second centre hole is through going and in such a case cooling medium will be ejected at the left end of the adapter 3 in figure 5. Thereby, it is made possible that the stud screw 5 also may be activated from the left end of the adapter 3 in figure 5.

15 In the embodiments described above the holder is of the type COROMANT CAPTO®. Within the scope of the invention it is of course feasible to have a number of other holders, and in exemplifying and non-restricting purpose ISO-cone, VARILOCK®-holder, cylindrical holders or prismatic holders should be mentioned.




20 In the embodiments described above the adapter 3; 3' is in the shape of a milling head. Within the scope of the invention other types of adapters are feasible, and in exemplifying and non-restricting purpose turning heads and drilling heads may be mentioned.


25 In the embodiment according to figures 1-7 the external threads 7, 9 of the stud screw 5 run in the same direction but have a different pitch. Within the scope of the invention it is also feasible that the threads run in different directions (turnscrew), and in such a case they may have the same pitch.


Claims

1. Tool coupling comprising a holder (1), an adapter (3; 3') for at least one cutting insert for chip removing machining and a separate element (5; 5') in order to detachably connect the holder (1) and the adapter (3; 3') with each other, said holder (1) being provided with a first serration (12), having mutually parallel grooves, and the adapter (3; 3') being provided with a second serration (16), having mutually parallel grooves, characterized in, that the first serration (12) is located in a plane having an extension essentially perpendicular to a longitudinal centre axis (13) of the tool coupling, and that the second serration (16) is located in a plane having an extension essentially perpendicular to said longitudinal centre axis (13).
2. Tool coupling according to claim 1, characterized in, that the connecting element constitutes a screw (5; 5') having a first external thread (7; 7') that in active position is in engagement with an internal thread (15) of the holder (1).
3. Tool coupling according to claim 2, characterized in, that the holder (1) and the adapter (3; 3') have openings (14, 17; 14, 17') for the screw (5; 5') in the planes where the serrations (12, 16) are located, that said openings (14, 17; 14, 17') have an oval cross section, and that the openings (14, 17; 14, 17') have a larger cross dimension in the direction perpendicular to the grooves of the serrations (12, 16) than in the direction parallel to the grooves of the serrations (12, 16).
4. Tool coupling according to any of the claims 1-3, characterized in, that the connecting element (5; 5') has an axially extending, internal, centrally located cooling passage (6; 6').
5. Tool coupling according to claim 4, characterized in, that the connecting element constitutes a stud screw (5) having two external threads (7, 9) at its respective ends, and that the second thread (9) cooperates with an internal thread (18) of the adapter (3), and that the cooling passage (6) extends through the stud screw (5).
6. Tool coupling according to claim 4, characterized in, that the connecting element constitutes a screw (5') having a head (8'), that the cooling passage (6') terminates within the screw (5'), that branch cooling passages (21') connect the cooling passage (6') with the circumferential surface of the screw (5'), and that the head (8') of the screw (5') cooperates with a shoulder (20') of the adapter (3').

7. Tool coupling according to claim 5, characterized in, that the stud screw (5) has two external threads (7, 9) that run in the same direction and have a different pitch.
- 5
8. Holder (1) intended to be a part of a tool coupling according to any of the claims 1-7, said holder (1) having a first serration (12) with mutually parallel grooves, and means (14, 15) to receive a connecting element (5; 5'), characterized in, that the first serration (12) is located in a plane having an extension essentially perpendicular to a longitudinal centre axis (13) of the holder (1).
- 10
9. Adapter (3; 3') intended to be a part of a tool coupling according to any of the claims 1-7, said adapter (3; 3') having a second serration (16) with mutually parallel grooves, and means (17, 18; 17', 18') to receive a connecting element (5; 5'),
- 15
- characterized in, that the second serration (16) is located in a plane having an extension essentially perpendicular to a longitudinal centre axis (13) of the adapter (3; 3').













FIG 13



# 1

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/SE 00/00270

### A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B23B 31/11, B23B 29/08  
According to International Patent Classification (IPC) or to both national classification and IPC

### B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B23B, B23Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC

### C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	Patent Abstracts of Japan, abstract of JP 60-118401 A (MITSUBISHI KINZOKU KK), 25 June 1985 (25.06.85), Figures 1,2	1,2,8-9
Y	--	4-5
X	US 9911411 A (SANDVIK AB), 11 March 1999 (11.03.99), figure 1, abstract	1,8,9
Y	US 4632614 A (RALL ET AL.), 30 December 1986 (30.12.86), column 6, line 53 - line 62, figure 1, abstract	4-5
	--	

☒ Further documents are listed in the continuation of Box C. ☒ See patent family annex.

<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p>	<p>"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&amp;" document member of the same patent family</p>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Date of the actual completion of the international search	Date of mailing of the international search report
31 May 2000	20 -07- 2000
Name and mailing address of the ISA Swedish Patent Office Box 5055, S-102 42 STOCKHOLM	Authorized officer Joakim Movander/OGU

**INTERNATIONAL SEARCH REPORT**

International application No.

PCT/SE 00/00270

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9310929 A1 (KOMET PRÄZISIONSWERKZEUGE ROBERT BREUNING GMBH), 10 June 1993 (10.06.93), figure 1, abstract  ----- -----	1-9

# INTERNATIONAL SEARCH REPORT

Information on patent family members

02/12/99

International application No.

PCT/SE 00/00270

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	9911411	A	11/03/99	NONE	
US	4632614	A	30/12/86	AT 19976 T	15/06/86
				CA 1225822 A	25/08/87
				DE 3228521 A,C	02/02/84
				EP 0101917 A,B	07/03/84
				SE 0101917 T3	
				ES 524580 A	01/05/84
				JP 1332763 C	28/08/86
				JP 59042206 A	08/03/84
				JP 60057984 B	18/12/85
				KR 8601709 B	18/10/86
				SU 1299487 A	23/03/87
				DE 3243948 A,C	05/07/84
				DE 3309922 A	20/09/84
WO	9310929	A1	10/06/93	AT 126462 T	15/09/95
				CA 2124802 A	10/06/93
				DE 4140301 A	09/06/93
				DE 59203313 D	00/00/00
				DK 615477 T	27/12/95
				EP 0615477 A,B	21/09/94
				SE 0615477 T3	
				ES 2076790 T	01/11/95
				HK 110896 A	05/07/96
				JP 7501494 T	16/02/95
				US 5555784 A	17/09/96